§ 28.120

- (2) 90 feet (27.4 meters) in length for a vessel 65 feet (19.8 meters) or more in length.
- (b) For each vessel less than 65 feet (19.8 meters) in length, an approved 20 inch (0.51 meters) or larger ring life buoy which is in serviceable condition and which was installed on board before September 15, 1991, may be used to meet the requirements of paragraph (a) of this section.

TABLE 28.115—THROWABLE FLOTATION
DEVICES

Vessel length	Devices required
Less than 16 feet (4.9 meters). 16 feet (4.9 meters) or more, but less than 26 feet (7.9 meters).	None. 1 buoyant cushion, or ring life buoy (Type IV PFD).
26 feet (7.9 meters) or more, but less than 65 feet (19.8 meters). 65 feet (19.8 meters) or more.	1 ring life buoy approval number starting with 160.009 or 160.050; orange; at least 24 inch (0.61 me- ters) size. 3 ring life buoys, approval number 160.050; orange; at least 24 inch (0.61 meters) size.

NOTE: Certain Type V PFDs are approved for use in substitution for Type IV PFDs, when used in accordance with the conditions stated in the Coast Guard approval label.

[CGD 88-079, 56 FR 40393, Aug. 14, 1991; 56 FR 47679, Sept. 20, 1991; 56 FR 49822, Oct. 1, 1991; CGD 95-012, 60 FR 48048, Sept. 18, 1995]

§ 28.120 Survival craft.

- (a) Except as provided in paragraphs (b) through (h) of this section and 28.305, each vessel must carry the survival craft specified in Table 28.120(a), Table 28.120(b), or Table 28.120(c), as appropriate for the vessel, in an aggregate capacity to accommodate the total number of individuals on board.
- (b) The requirements of this section do not apply to vessels less than 10.97 meters (36 feet) in length with 3 or fewer individuals on board which operate within 12 miles of the coastline.
- (c) A buoyant apparatus may be substituted instead of the requirements in this section for vessels 10.97 meters (36 feet) or more in length with 3 or fewer individuals on board which operate within 12 miles of the coastline.

- (d) Each survival craft installed on board a vessel before September 15, 1991, may continue to be used to meet the requirements of this section provided the survival craft is—
- (1) Of the same type as required in Tables 28.120(a), 28.120(b), or 28.120(c), as appropriate for the vessel type; and
- (2) Maintained in good and serviceable condition.
- (e) Each inflatable liferaft installed on board a vessel before September 15, 1991, may continue to be used to meet the requirements for an approved inflatable liferaft, provided the existing liferaft is—
- (1) Maintained in good and serviceable condition as required by Table 28.140; and
- (2) Equipped with the equipment pack required by Tables 28.120(a), 28.120(b), or 28.120(c), as appropriate for the vessel type. Where no equipment pack is specified in Tables 28.120(a), 28.120(b), or 28.120(c), a coastal service pack is the minimum required.
- (f) A lifeboat may be substituted for any survival craft required by this section, provided it is arranged and equipped in accordance with part 199 of this chapter.
- (g) The capacity of an auxiliary craft carried on board a vessel that is integral to and necessary for normal fishing operations will satisfy the requirements of this section for survival craft, except for an inflatable liferaft, provided the craft is readily accessible during an emergency and is capable of safely holding all individuals on board the vessel. If the auxiliary craft is equipped with a Coast Guard required capacity plate, the boat must not be loaded so as to exceed the rated capacity.
- (h) A vessel less than 10.97 meters (36 feet) in length that meets the flotation provisions of 33 CFR part 183 is exempt from the requirement for survival craft in paragraph (a) of this section for operation on—
- (1) Any waters within 12 miles of the coastline.
 - (2) Rivers.

TABLE 28.120(a)—SURVIVAL CRAFT FOR DOCUMENTED VESSELS

Area	Vessel type	Survival craft required
Beyond 50 miles of coastline	All	Inflatable liferaft with SOLAS A pack.

Coast Guard, DHS § 28.120

TABLE 28.120(a)—SURVIVAL CRAFT FOR DOCUMENTED VESSELS—Continued

Area	Vessel type	Survival craft required
Between 20–50 miles of coastline, cold waters		Inflatable liferaft with SOLAS B pack.
Between 20–50 miles of coastline, warm waters		Inflatable liferaft.
Beyond Boundary Line, between 12-20 miles of coast-	All	Inflatable liferaft.
line, cold waters.		
Beyond Boundary Line, within 12 miles of coastline,	10.97 meters (36 feet) or	Inflatable buoyant apparatus. See note 2.
cold waters.	more in length.	
Beyond Boundary Line, within 12 miles of coastline,	Less than 10.97 meters (36	Buoyant apparatus.
cold waters.	feet) in length.	See note 2.
Beyond Boundary Line, within 20 miles of coastline,	All	Life float. See note 2.
warm waters.		
Inside Boundary Line, cold waters; or Lakes, bays,		Inflatable buoyant apparatus.
sounds, cold waters; or Rivers, cold waters.	more in length.	See note 2.
Inside Boundary Line, cold waters; or Lakes, bays,	Less than 10.97 meters (36	Buoyant apparatus.
sounds, cold waters; or Rivers, cold waters.	feet) in length.	See note 2.
Inside Boundary Line, warm waters; or Lakes, bays,	All	None.
sounds, warm waters; or Rivers, warm waters.		
Great Lakes, cold waters	10.97 meters (36 feet) or	Inflatable buoyant apparatus.
	more in length.	See note 2.
Great Lakes, cold waters	Less than 10.97 meters (36	Buoyant apparatus.
	feet) in length.	See note 2.
Great Lakes, beyond 3 miles of coastline, warm waters	All	Buoyant apparatus. See note 2.
Great Lakes, within 3 miles of coastline, warm waters	All	None.

Note: 1. The hierarchy of survival craft in descending order is lifeboat, inflatable liferaft with SOLAS A pack, inflatable liferaft with SOLAS B pack, inflatable liferaft with coastal service pack, inflatable buoyant apparatus, life float, buoyant apparatus. A survival craft higher in the hierarchy may be substituted for any survival craft required in this table.

2. If a vessel carriers 3 or fewer individuals within 12 miles of the coastline, see § 28.120 (b) and (c) for carriage substitution.

TABLE 28.120(b)—SURVIVAL CRAFT FOR UNDOCUMENTED VESSELS WITH NOT MORE THAN 16 INDIVIDUALS ON BOARD

Area	Vessel type	Survival craft required
Beyond 20 miles of coastline	All	Inflatable buoyant apparatus.
Beyond Boundary Line, between 12–20 miles of coast- line, <i>cold</i> waters.	All	Inflatable buoyant apparatus.
Beyond Boundary Line, within 12 miles of coastline,	10.97 meters (36 feet) or	Buoyant apparatus.
cold waters.	more in length.	
Beyond Boundary Line, within 12 miles of coastline, cold waters.	Less than 10.97 meters (36 feet) in length.	Buoyant apparatus. See note 2.
Beyond Boundary Line, within 20 miles of coastline,	All	Life float. See note 2.
warm waters. Inside Boundary Line, cold waters; or Lakes, bays,	10.97 meters (36 feet) or	Buoyant apparatus.
sounds, <i>cold</i> waters; or rivers, <i>cold</i> water.	more in length.	Buoyani apparatus.
Inside Boundary Line, cold waters; or Lakes, bays,	Less than 10.97 meters (36	Buoyant apparatus
sounds, cold waters; or Rivers, <i>cold</i> water. Inside Boundary Line, <i>warm</i> waters; or Lakes, bays,	feet) in length.	See note 2.
sounds, warm waters; or Rivers, warm waters.		
Great Lakes, cold waters	All	Buoyant apparatus. See note 2.
Great Lakes, beyond 3 miles of coastline warm waters	All	Buoyant apparatus.
		See note 2.
Great Lakes, within 3 miles of coastline warm waters	All	None.

Note: 1. The hierarchy of survival craft in descending order is lifeboat, inflatable liferaft with SOLAS A pack, inflatable liferaft with SOLAS B pack, inflatable liferaft with coastal service pack, inflatable buoyant apparatus, life float, buoyant apparatus. A survival craft higher in the hierarchy may be substituted for any survival craft required in this table.

2. If a vessel carries 3 or fewer individuals within 12 miles of the coastline, see § 28.120 (b) and (c) for carriage substitution.

TABLE 28.120(c)—SURVIVAL CRAFT FOR UNDOCUMENTED VESSELS WITH MORE THAN 16 INDIVIDUALS ON BOARD

Area	Vessel type	Survival craft required
Beyond 50 miles of coastline	All	Inflatable liferaft with SOLAS A pack. Inflatable liferaft with SOLAS B pack. Inflatable liferaft. Inflatable liferaft.
Beyond Boundary Line, within 12 miles of coastline, cold waters.	10.97 meters (36 feet) or more in length.	Inflatable bouyant apparatus.
Beyond Boundary Line, within 12 miles of coastline, cold waters.	Less than 10.97 meters (36 feet) in length.	Buoyant apparatus.

§ 28.125

TABLE 28.120(c)—SURVIVAL CRAFT FOR UNDOCUMENTED VESSELS WITH MORE THAN 16 INDIVIDUALS ON BOARD—Continued

Area	Vessel type	Survival craft required
Beyond Boundary Line, within 20 miles of coastline, warm waters.	All	Life float.
Inside Boundary Line, <i>cold</i> waters; or Lakes, bays, sounds, <i>cold</i> waters; or Rivers, <i>cold</i> waters.	10.97 meters (36 feet) or more in length.	Inflatable buoyant apparatus.
Inside Boundary Line, cold waters; or Lakes, bays, sounds, cold waters; or Rivers, cold waters.	Less than 10.97 meters (36 feet) in length.	Buoyant apparatus.
Inside Boundary Line, warm waters; or Lakes, bays, sounds, warm waters; or Rivers, warm waters.	All	None.
Great Lakes, cold waters	10.97 meters (36 feet) or more in length.	Inflatable buoyant apparatus.
Great Lakes, cold waters	Less than 10.97 meters (36 feet) in length.	Buoyant apparatus.
Great Lakes, beyond 3 miles of coastline warm waters Great Lakes, within 3 miles of coastline warm waters	All	Buoyant apparatus. None.

Note: 1. The hierarchy of survival craft in descending order is lifeboat, liferaft with SOLAS A pack, Inflatable liferaft with SOLAS A pack, liferaft with SOLAS B pack, inflatable liferaft with SOLAS B pack, inflatable buoyant apparatus, life float, buoyant apparatus. A survival craft higher in the hierarchy may be substituted for any survival craft required in this table.

[CGD 96-046, 61 FR 57273, Nov. 5, 1996; CGD 96-046, 61 FR 68162, Dec. 27, 1996, as amended by CGD 96-046, 62 FR 46676, Sept. 4, 1997; USCG-2002-13058, 67 FR 61278, Sept. 30, 2002]

§28.125 Stowage of survival craft.

- (a) Each inflatable liferaft required to be equipped with a SOLAS A or a SOLAS B equipment pack must be stowed so as to float free and automatically inflate in the event the vessel sinks.
- (b) Each inflatable liferaft, inflatable buoyant apparatus, and any auxiliary craft used in their place, must be kept readily accessible for launching or be stowed so as to float free in the event the vessel sinks.
- (c) Each hydrostatic release unit used in a float-free arrangement must be approved under part 160, subpart 160.062 of this chapter.
- (d) Each float-free link used with a buoyant apparatus or with a life float must be certified to meet part 160, subpart 160.073 of this chapter.

§ 28.130 Survival craft equipment.

- (a) General. Each item of survival craft equipment must be of good quality, effective for the purpose it is intended to serve, and secured to the craft.
- (b) Inflatable liferafts. Each inflatable liferaft must have one of the following equipment packs as shown by the markings on its container:
 - (1) Coastal Service;
- (2) SOLAS B Pack (formerly "Limited Service"); or

- (3) SOLAS A Pack (formerly "Ocean Service").
- (c) Each life float and buoyant apparatus must be fitted with a lifeline, pendants, a painter, and a floating electric water light approved under part 161 subpart 161.010 of this chapter.
- (d) Other survival craft. A vessel must not carry survival craft other than inflatable liferafts, life floats, inflatable buoyant apparatus, or buoyant apparatus, such as lifeboats or rigid liferafts, unless the survival craft and launching equipment comply with the requirements for installation, arrangement, equipment, and maintenance contained in 46 CFR part 199.

[CGD 88-079, 56 FR 40393, Aug. 14, 1991, as amended by CGD 84-069, 63 FR 52813, Oct. 1, 1993

\$28.135 Lifesaving equipment markings.

- (a) Except as provided in paragraph (d) of this section, lifesaving equipment carried aboard a vessel pursuant to the requirements of this subpart or part 25, subpart 25.25 of this chapter must be marked as specified in table 28.135.
- (b) Lettering used in lifesaving equipment markings must be in block capital letters.
- (c) Retroreflective markings required by this section must be with material approved under part 164, subpart 164.018